


ISO 7380-1 A2 TX
Flachrundkopfschrauben Innensechsrund, Vollgewinde

ISO 7380-1
A2

ISO 7380-1 A2 TX
Button head screws with six lobe drive with fullthread

d	M 6	M 8	M 10	M 12
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
3				
4				
5				
6	738012T6 6			
8	738012T6 8	738012T8 8		
10	738012T6 10	738012T8 10		
12	738012T6 12	738012T8 12	738012T10 12	
14	738012T6 14	738012T8 14	738012T10 14	
16	738012T6 16	738012T8 16	738012T10 16	738012T12 16
18	738012T6 18	738012T8 18	738012T10 18	738012T12 18
20	738012T6 20	738012T8 20	738012T10 20	738012T12 20
22	738012T6 22	738012T8 22	738012T10 22	738012T12 22
25	738012T6 25	738012T8 25	738012T10 25	738012T12 25
30	738012T6 30	738012T8 30	738012T10 30	738012T12 30
35	738012T6 35	738012T8 35	738012T10 35	738012T12 35
40	738012T6 40	738012T8 40	738012T10 40	738012T12 40
45	738012T6 45	738012T8 45	738012T10 45	738012T12 45
50	738012T6 50	738012T8 50	738012T10 50	738012T12 50
55	738012T6 55	738012T8 55	738012T10 55	738012T12 55
60	738012T6 60	738012T8 60	738012T10 60	738012T12 60
65	738012T6 65	738012T8 65	738012T10 65	738012T12 65
70	738012T6 70	738012T8 70	738012T10 70	738012T12 70
75	738012T6 75	738012T8 75	738012T10 75	738012T12 75
80	738012T6 80	738012T8 80	738012T10 80	738012T12 80
90	738012T6 90	738012T8 90	738012T10 90	738012T12 90
100	738012T6 100	738012T8 100	738012T10 100	738012T12 100
110		738012T8 110	738012T10 110	738012T12 110
120	738012T6 120	738012T8 120	738012T10 120	738012T12 120



Auf Wunsch Fremdüberwacht
von M6 bis einschl. M12
lieferbar.
- "0" = reduzierte
Belastbarkeit

quality inspection from M6
including to M12 available on
demand.

- "0" = reduced load capacity

☞	500	500		
	>= 18	>= 10	100	50
	200	200	>= 50	>= 75
	>= 20	>= 65	50	25
	500	100		
	>= 22	>= 100		
	200	50		
	>= 45			
100				
dk	10,5	14	17,5	21
k	3,3	4,4	5,5	6,6
t	2,1	2,7	3,4	4,2
Antrieb	TX30	TX40	TX50	TX55