


ISO 4762 A2
Zylinderschrauben mit Innensechskant, Teilgewinde

ISO 4762 A2
Hexagon socket head cap screws, partial thread

ISO 4762
A2

Alternative Norm
ehemals DIN 912

d	M 1,6	M 2	M 2,5	M 3	M 4	M 5
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
18	47622016 18					
20	47622016 20					
22		476222 22		476223 22		
25		476222 25		476223 25		
30		476222 30	4762225 30	476223 30	476224 30	476225 30
35			4762225 35	476223 35	476224 35	476225 35
40			4762225 40	476223 40	476224 40	476225 40
45				476223 45	476224 45	476225 45
50				476223 50	476224 50	476225 50
55				476223 55	476224 55	476225 55
60				476223 60	476224 60	476225 60
65				476223 65	476224 65	476225 65
70				476223 70	476224 70	476225 70
75					476224 75	476225 75
80					476224 80	476225 80
85						476225 85
90					476224 90	476225 90
95						476225 95
100					476224 100	476225 100
110						476225 110
120						476225 120
130						476225 130
140						476225 140
150						
160						
170						
180						
190						
200						
210						
220						
230						
240						
250						
260						
270						
280						
290						
300						
320						



b = nach Norm

Weitere Abmessungen auf
Anfrage lieferbar!

Auf Wunsch Fremdüberwacht
von M6 bis einschl. M24
lieferbar.

b = at Norm

Other dimensions on demand!

quality inspection from M6
including to M24 available on
demand.

	500	500	500 >= 35 1000	1000 >= 35 500 >= 50 200	500 >= 35 200 >= 60 100	200 >= 65 100
dk	3	3,8	4,5	5,5	7	8,5
k	1,6	2	2,5	3	4	5
Antrieb	SW 1,5	SW 1,5	SW 2	SW 2,5	SW 3	SW 4