

DIN 966

A4

Alternative Norm
ersetzt durch ISO 7047

DIN 966 A4 PZ

Linsensenkschrauben mit Kreuzschlitz

DIN 966 A4 PZ

Cross recessed raised countersunk head screws



- TX Form siehe ISO 14584

- TX type see ISO 14584

DIN

| d | M 2 | M 2,5 | M 3 | M 4 |
|-------------|---------------------|---------------------|---------------------|---------------------|
| l/mm | Art. Nr. / Item no. | Art. Nr. / Item no. | Art. Nr. / Item no. | Art. Nr. / Item no. |
| 3 | 0966402 3 | | | |
| 4 | 0966402 4 | 09664025 4 | 0966403 4 | |
| 5 | 0966402 5 | 09664025 5 | 0966403 5 | 0966404 5 |
| 6 | 0966402 6 | 09664025 6 | 0966403 6 | 0966404 6 |
| 8 | 0966402 8 | 09664025 8 | 0966403 8 | 0966404 8 |
| 10 | 0966402 10 | 09664025 10 | 0966403 10 | 0966404 10 |
| 12 | 0966402 12 | 09664025 12 | 0966403 12 | 0966404 12 |
| 14 | 0966402 14 | 09664025 14 | 0966403 14 | 0966404 14 |
| 16 | 0966402 16 | 09664025 16 | 0966403 16 | 0966404 16 |
| 18 | 0966402 18 | 09664025 18 | 0966403 18 | 0966404 18 |
| 20 | 0966402 20 | 09664025 20 | 0966403 20 | 0966404 20 |
| 22 | | | 0966403 22 | 0966404 22 |
| 25 | 0966402 25 | 09664025 25 | 0966403 25 | 0966404 25 |
| 28 | | | 0966403 28 | 0966404 28 |
| 30 | 0966402 30 | 09664025 30 | 0966403 30 | 0966404 30 |
| 35 | | | 0966403 35 | 0966404 35 |
| 40 | | | 0966403 40 | 0966404 40 |
| 45 | | | 0966403 45 | 0966404 45 |
| 50 | | | 0966403 50 | 0966404 50 |
| 55 | | | | 0966404 55 |
| 60 | | | | 0966404 60 |
| 65 | | | | 0966404 65 |
| 70 | | | | 0966404 70 |
| 75 | | | | 0966404 75 |
| 80 | | | | 0966404 80 |
| 85 | | | | |
| 90 | | | | |
| 95 | | | | |
| 100 | | | | |

| | | | | |
|----------------|------|------|------|-----|
| | 1000 | 1000 | 500 | 500 |
| dk | 3,8 | 4,7 | 5,6 | 7,5 |
| k | 1,2 | 1,5 | 1,65 | 2,2 |
| Antrieb | PZ1 | PZ1 | PZ1 | PZ2 |