

# ISO 4762

## A4-80

Alternative Norm  
ehemals DIN 912

# ISO 4762 A4-80

## Zylinderschrauben mit Innensechskant, Vollgewinde

### ISO 4762 A4-80

Hexagon socket head cap screws, fullthread



Auf Wunsch Fremdüberwacht  
von M6 bis einschl. M24  
lieferbar.

quality inspection from M6  
including to M24 available on  
demand.

d	M 4	M 5	M 6	M 8	M 10
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
4	47624804 4				
5	47624804 5	47624805 5			
6	47624804 6	47624805 6	47624806 6		
8	47624804 8	47624805 8	47624806 8	47624808 8	
10	47624804 10	47624805 10	47624806 10	47624808 10	
12	47624804 12	47624805 12	47624806 12	47624808 12	476248010 12
14	47624804 14	47624805 14	47624806 14	47624808 14	476248010 14
16	47624804 16	47624805 16	47624806 16	47624808 16	476248010 16
18	47624804 18	47624805 18	47624806 18	47624808 18	476248010 18
20	47624804 20	47624805 20	47624806 20	47624808 20	476248010 20
22	47624804 22	47624805 22	47624806 22	47624808 22	476248010 22
25	47624804 25	47624805 25	47624806 25	47624808 25	476248010 25
30			47624806 30	47624808 30	476248010 30
35				47624808 35	476248010 35
40					476248010 40
45					
50					
55					
60					
65					
70					
75					
80					
90					

	1000 ≥ 20 500	500 ≥ 25 200	500 ≥ 14 200	500 ≥ 14 200 ≥ 25 100	100
dk	7	8,5	10	13	16
k	4	5	6	8	10
Antrieb	SW 3	SW 4	SW 5	SW 6	SW 8