

ISO 4762 A2  
Zylinderschrauben mit Innensechskant, Vollgewinde

ISO 4762 A2  
Hexagon socket head cap screws, fullthread

ISO 4762  
A2

Alternative Norm  
ehemals DIN 912

d	M 5	M 6	M 8	M 10	M 12
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
3					
4					
5	476225 5				
6	476225 6	476226 6			
8	476225 8	476226 8	476228 8		
10	476225 10	476226 10	476228 10		
12	476225 12	476226 12	476228 12	4762210 12	
14	476225 14	476226 14	476228 14	4762210 14	
16	476225 16	476226 16	476228 16	4762210 16	4762212 16
18	476225 18	476226 18	476228 18	4762210 18	4762212 18
20	476225 20	476226 20	476228 20	4762210 20	4762212 20
22	476225 22	476226 22	476228 22	4762210 22	4762212 22
25	476225 25	476226 25	476228 25	4762210 25	4762212 25
30	476225 30/30	476226 30	476228 30	4762210 30	4762212 30
35	476225 35/35	476226 35/35	476228 35	4762210 35	4762212 35
40	476225 40/40	476226 40/40	476228 40/40	4762210 40	4762212 40
45	476225 45/45	476226 45/45	476228 45/45	4762210 45/45	4762212 45
50	476225 50/50	476226 50/50	476228 50/50	4762210 50/50	4762212 50
55		476226 55/55	476228 55/55	4762210 55/55	4762212 55/55
60	476225 60/60	476226 60/60	476228 60/60	4762210 60/60	4762212 60/60
65	476225 65/65		4762208 65/65		
70	476225 70/70	476226 70/70	476228 70/70	4762210 70/70	4762212 70/70
75					
80	476225 80/80	476226 80/80	476228 80/80	4762210 80/80	4762212 80/80
85					
90		476226 90/90	476228 90/90	4762210 90/90	4762212 90/90
95					
100		476226 100/100	476228 100/100	4762210 100/100	4762212 100/100
120			476228 120/120		



Auf Wunsch Fremdüberwacht  
von M6 bis einschl. M24  
lieferbar.

quality inspection from M6  
including to M24 available on  
demand.

	500 ≥ 25 200 ≥ 60 100	500 ≥ 14 200 ≥ 45 100	500 ≥ 14 200 ≥ 25 100 ≥ 100 50	100 ≥ 50 50	50 ≥ 80 25
dk	8,5	10	13	16	18
k	5	6	8	10	12
Antrieb	SW 4	SW 5	SW 6	SW 8	SW 10

ISO