

DIN 966 A4 PH
Linsensenkschrauben mit Kreuzschlitz

DIN 966 A4 PH
Cross recessed raised countersunk head screws

DIN 966
A4

Alternative Norm
 ersetzt durch ISO 7047

d	M 5	M 6	M 8
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
3			
4			
5			
6	096645 6		
8	096645 8	096646 8	
10	096645 10	096646 10	
12	096645 12	096646 12	096648 12
14	096645 14	096646 14	
16	096645 16	096646 16	096648 16
18	096645 18	096646 18	
20	096645 20	096646 20	096648 20
22	096645 22	096646 22	
25	096645 25	096646 25	096648 25
28	096645 28	096646 28	
30	096645 30	096646 30	096648 30
35	096645 35	096646 35	096648 35
40	096645 40	096646 40	096648 40
45	096645 45	096646 45	096648 45
50	096645 50	096646 50	096648 50
55	096645 55	096646 55	
60	096645 60	096646 60	096648 60
65	096645 65	096646 65	
70	096645 70	096646 70	096648 70
75	096645 75	096646 75	
80	096645 80	096646 80	096648 80
85	096645 85	096646 85	
90	096645 90	096646 90	
95	096645 95	096646 95	
100	096645 100	096646 100	



- TX Form siehe ISO 14584

- TX type see ISO 14584

	500 ≥ 45 200	500 ≥ 22 200 ≥ 45 500 ≥ 50 200	200 ≥ 60 100
dk	9,2	11	14,5
k	2,5	3	4
Antrieb	PH2	PH3	PH4

DIN