



VOOL LMC SPECIFICATIONS

FEATURES

Remote connectivity	OCPP 1.6, OCPP 2.0
Integration	Solar ¹ , batteries ¹
Market price monitoring	EU markets
Supported no. of chargers	64 chargers
Load management	Dynamic Load Management (DLM), Dynamic Phase Management (DPM), Multipoint Load Management, Multilevel Load Management
DLM response time	Below 50ms
Firmware updates	Automatic, OTA

EXTERNAL INTERFACES

Internet connectivity	4G, Wi-Fi (IEEE 802.11 b/g/n), Ethernet 10/100
External meter	Modbus RTU(RS485), Modbus TCP/UDP
Local device network	CAN
Current input	3x external current transformer
Voltage input	3 phase 230/400 VAC

SAFETY

Compliance	LVD
Electrical protection	Protection CLASS I, overvoltage category III

GENERAL SPECIFICATIONS

Supply voltage	90-265 VAC
AC frequency	50 or 60Hz
Dimensions (W x H x D)	61 x 87 x 77 mm
Weight	0.3 kg
Mounting options	DIN-rail, custom
Operating temperature	-20...+55 C
Enclosure environmental rating	Indoor / IP22
Standards	LVD 2014/35/EU, EMC 2014/30/EU
Standard warranty	5 years

¹ Coming soon

www.vool.com

Get in touch: info@vool.com

VOOL