

Patentivanteet



**Laaja
valikoima!**

a-collection
- laatua oikeaan hintaan

Patenttivanne

Sinkitty



LVI numero	Koko mm	Reiän Ø mm	Reikäväli mm	Max. kuorma kN	m/ltk
323 0870	12×1,00	5,5	15	0,85	10
323 0871	12×1,00	5,5	15	0,85	25
323 0872	17×1,00	7,0	20	1,15	10
323 0873	17×1,00	7,0	20	1,15	25
323 0874	26×1,00	8,5	26	2,55	10

Muovitettu



LVI numero	Koko mm	Reiän Ø mm	Reikäväli mm	Max. kuorma kN	Väri	m/ltk
323 0879	12×1,00	5,5	15	0,85	Harmaa	10
323 0880	17×1,00	5,5	15	0,85	Harmaa	10
323 0881	12×1,00	7,0	20	1,15	Valk.	10
323 0882	17×1,00	7,0	20	1,15	Valk.	10

Alumiini



LVI numero	Koko mm	Reiän Ø mm	Reikäväli mm	Max. kuorma kN	m/ltk
323 0883	12×1,00	5,5	15	0,40	10
323 0884	17×1,00	7,0	20	0,85	10

HST



LVI numero	Koko mm	Reiän Ø mm	Reikäväli mm	Max. kuorma kN	m/ltk
323 0875	17×1,00	7,0	20	1,50	10
323 0876	17×1,00	7,0	20	1,50	25
323 0877	26×1,00	9,0	26	3,10	10
323 0878	26×1,00	9,0	26	3,10	25
323 0626	17×0,50	7,0	20	0,65	25

TR-vanne HST



LVI numero	Koko mm	Reiän Ø mm	Reikäväli mm	Max. kuorma kN	m/ltk
323 0632	25×1,00	8,0	27	2,35	25

Varmuuskerroin = 3