

DIN 603

A2


Alternative Norm
ersetzt durch ISO 8677

DIN 603 A2

Flachrundschauben mit Vierkantansatz, Teilgewinde

DIN 603 A2

Mushroom head square neck bolts, partial thread



DIN

b = nach Norm

Auf Wunsch Fremdüberwacht
von M6 bis einschl. M16
lieferbar.

b = at Norm

quality inspection from M6
including to M16 available on
demand.

d	M 5	M 6	M 8	M 10	M 12	M 16
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
25		060326 25				
30	060325 30	060326 30	060328 30			
35	060325 35	060326 35	060328 35	0603210 35		
40	060325 40	060326 40	060328 40	0603210 40		0603216 40
45	060325 45	060326 45	060328 45	0603210 45		0603216 45
50	060325 50	060326 50	060328 50	0603210 50		0603216 50
55	060325 55	060326 55	060328 55	0603210 55	0603212 55	0603216 55
60	060325 60	060326 60	060328 60	0603210 60	0603212 60	0603216 60
65	060325 65	060326 65	060328 65	0603210 65	0603212 65	0603216 65
70	060325 70	060326 70	060328 70	0603210 70	0603212 70	0603216 70
75	060325 75	060326 75	060328 75	0603210 75	0603212 75	0603216 75
80	060325 80	060326 80	060328 80	0603210 80	0603212 80	0603216 80
90		060326 90	060328 90	0603210 90	0603212 90	0603216 90
100		060326 100	060328 100	0603210 100	0603212 100	0603216 100
110		060326 110	060328 110	0603210 110	0603212 110	0603216 110
120		060326 120	060328 120	0603210 120	0603212 120	0603216 120
130		060326 130	060328 130	0603210 130	0603212 130	0603216 130
140		060326 140	060328 140	0603210 140	0603212 140	0603216 140
150		060326 150	060328 150	0603210 150	0603212 150	0603216 150
160			060328 160	0603210 160	0603212 160	0603216 160
170			060328 170			
180			060328 180	0603210 180	0603212 180	0603216 180
190			060328 190		0603212 190	
200			060328 200	0603210 200	0603212 200	0603216 200
220				0603210 220	0603212 220	0603216 220
240				0603210 240	0603212 240	0603216 240
260				0603210 260	0603212 260	0603216 260
280				0603210 280	0603212 280	0603216 280
300				0603210 300	0603212 300	0603216 300

	200	200 ≥ 45 100	100 ≥ 70 50 ≥ 160 25 ≥ 170 50	100 ≥ 50 50	50 ≥ 110 25 ≥ 130 50	25
dk	13,55	16,55	20,65	24,65	30,65	38,8
k	3,3	3,88	4,88	5,38	6,95	8,95
v	5,48	6,48	8,58	10,58	12,7	16,7
f	4,1	4,6	5,6	6,6	8,75	12,9