


# DIN 7504 K A2

Alternative Norm  
ersetzt durch ISO 15480

# DIN 7504 K A2 Bohrschrauben mit Sechskantkopf und Bund, Form K

DIN 7504 K A2  
Self drilling screws hexagon flange head type K



Achtung: nur für Weichmetalle

Attention: only for soft metals

DIN

d	3,5	3,9	4,2	4,8	5,5	6,3
<b>l/mm</b>	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
<b>9,5</b>	75042K35 95					
<b>13</b>	75042K35 13	75042K39 13	75042K42 13	75042K48 13	75042K55 13	75042K63 13
<b>16</b>	75042K35 16	75042K39 16	75042K42 16	75042K48 16	75042K55 16	75042K63 16
<b>19</b>	75042K35 19	75042K39 19	75042K42 19	75042K48 19	75042K55 19	75042K63 19
<b>22</b>	75042K35 22	75042K39 22	75042K42 22	75042K48 22	75042K55 22	75042K63 22
<b>25</b>	75042K35 25	75042K39 25	75042K42 25	75042K48 25	75042K55 25	75042K63 25
<b>28</b>					75042K55 28	
<b>30</b>					75042K55 30	
<b>32</b>		75042K39 32	75042K42 32	75042K48 32	75042K55 32	75042K63 32
<b>35</b>				75042K48 35	75042K55 35	
<b>38</b>		75042K39 38	75042K42 38	75042K48 38	75042K55 38	75042K63 38
<b>40</b>					75042K55 40	
<b>45</b>			75042K42 45	75042K48 45	75042K55 45	75042K63 45
<b>50</b>			75042K42 50	75042K48 50	75042K55 50	75042K63 50
<b>60</b>				75042K48 60	75042K55 60	75042K63 60
<b>70</b>				75042K48 70	75042K55 70	75042K63 70
<b>75</b>					75042K55 75	75042K63 75
<b>80</b>				75042K48 80	75042K55 80	75042K63 80
<b>90</b>				75042K48 90	75042K55 90	75042K63 90
<b>100</b>				75042K48 100	75042K55 100	75042K63 100
<b>110</b>					75042K55 110	75042K63 110
<b>120</b>					75042K55 120	
<b>125</b>					75042K55 125	75042K63 125
<b>130</b>					75042K55 130	
<b>140</b>					75042K55 140	
<b>150</b>					75042K55 150	75042K63 150

	1000	1000 ≥ 38 500	1000 ≥ 38 500 ≥ 50 200	500 ≥ 60 200	500 ≥ 50 200 ≥ 125 100 ≥ 130 200	500 ≥ 50 200 ≥ 100 100
<b>e</b>	5,96	5,96	7,59	8,71	8,71	10,95
<b>dc</b>	8,3	8,3	8,8	10,5	11	13,2
<b>k</b>	3,45	3,45	4,25	4,45	5,45	6,45
<b>p</b>	1,2	1,3	1,4	1,5	1,7	2
<b>dp</b>	2,8	3,1	3,6	4,1	4,8	5,8
<b>Bohrbe.</b>	0,7-2,25	0,7-2,4	1,75-3,0	1,75-4,4	1,75-5,25	2,0-6,0
<b>Antrieb</b>	SW 5,5	SW 5,5	SW 7	SW 8	SW 8	SW 10