

ISO 10642 A2
Senkschrauben mit Innensechskant und Vollgewinde

ISO 10642 A2
Hexagon socket countersunk head screws with fullthread

ISO 10642
A2
Alternative Norm
equivalents DIN 7991

d	M 2	M 2,5	M 3	M 4
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
3	1064222 3	10642225 3		
4	1064222 4	10642225 4	1064223 4	
5	1064222 5	10642225 5	1064223 5	1064224 5
6	1064222 6	10642225 6	1064223 6	1064224 6
8	1064222 8	10642225 8	1064223 8	1064224 8
10	1064222 10	10642225 10	1064223 10	1064224 10
12	1064222 12	10642225 12	1064223 12	1064224 12
14	1064222 14	10642225 14	1064223 14	1064224 14
16	1064222 16	10642225 16	1064223 16	1064224 16
18			1064223 18	1064224 18
20	1064222 20	10642225 20	1064223 20	1064224 20
22			1064223 22	1064224 22
25			1064223 25	1064224 25
30			1064223 30	1064224 30
35			1064223 35	1064224 35
40			1064223 40	1064224 40
45			1064223 45	1064224 45
50			1064223 50	1064224 50
55				1064224 55
60				1064224 60
65				
70				
75				
80				
90				
100				
110				
120				
130				
140				
150				
160				
170				
180				
190				
200				



Auf Wunsch Fremdüberwacht
von M6 bis einschl. M24
lieferbar.
- "0" = reduzierte
Belastbarkeit

quality inspection from M6
including to M24 available on
demand.
- "0" = reduced load capacity

	1000	1000	1000 ≥ 35 500 ≥ 50 200	1000 ≥ 20 500 ≥ 35 200 ≥ 60 100
dk	4	5	6,72	8,96
k	1,2	1,55	1,86	2,48
Antrieb	SW 1,3	SW 1,5	SW 2	SW 2,5