


ISO 4762 A4-80

Alternative Norm
ehemals DIN 912

ISO 4762 A4-80 Zylinderschrauben mit Innensechskant, Teilgewinde

ISO 4762 A4-80
Hexagon socket head cap screws, partial thread



d	M 4	M 5	M 6	M 8	M 10
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
30	47624804 30	47624805 30			
35	47624804 35	47624805 35	47624806 35		
40	47624804 40	47624805 40	47624806 40	47624808 40	
45	47624804 45	47624805 45	47624806 45	47624808 45	476248010 45
50	47624804 50	47624805 50	47624806 50	47624808 50	476248010 50
55	47624804 55	47624805 55	47624806 55	47624808 55	476248010 55
60	47624804 60	47624805 60	47624806 60	47624808 60	476248010 60
65		47624805 65	47624806 65	47624808 65	476248010 65
70		47624805 70	47624806 70	47624808 70	476248010 70
75		47624805 75	47624806 75	47624808 75	476248010 75
80		47624805 80	47624806 80	47624808 80	476248010 80
90			47624806 90	47624808 90	476248010 90
100			47624806 100	47624808 100	476248010 100
110			47624806 110	47624808 110	476248010 110
120			47624806 120	47624808 120	476248010 120
130			47624806 130	47624808 130	476248010 130
140			47624806 140	47624808 140	476248010 140
150			47624806 150	47624808 150	476248010 150
160				47624808 160	476248010 160
170				47624808 170	476248010 170
180				47624808 180	476248010 180
190				47624808 190	476248010 190
200				47624808 200	476248010 200

b = nach Norm

Weitere Abmessungen auf
Anfrage lieferbar!

Auf Wunsch Fremdüberwacht
von M6 bis einschl. M24
lieferbar.

b = at Norm

Other dimensions on demand!

quality inspection from M6
including to M24 available on
demand.

	500 ≥ 35 200 ≥ 60 100	200 ≥ 60 100	200 ≥ 45 100	100 ≥ 80 50 ≥ 170 25	100 ≥ 50 50 ≥ 170 25
dk	7	8,5	10	13	16
k	4	5	6	8	10
Antrieb	SW 3	SW 4	SW 5	SW 6	SW 8