


ISO 7380-2 A2 mit Flansch TX
Flachrundkopfschrauben Innensechsrund mit Flansch, Vollgewinde

ISO 7380-2
A2

ISO 7380-2 A2 with flange TX
Button head screws TX-drive flange with fullthread

d	M 6	M 8	M 10	M 12
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
3				
4				
5				
6	738022T6 6			
8	738022T6 8	738022T8 8		
10	738022T6 10	738022T8 10		
12	738022T6 12	738022T8 12	738022T10 12	
14	738022T6 14	738022T8 14	738022T10 14	
16	738022T6 16	738022T8 16	738022T10 16	738022T12 16
18	738022T6 18	738022T8 18	738022T10 18	738022T12 18
20	738022T6 20	738022T8 20	738022T10 20	738022T12 20
22	738022T6 22	738022T8 22	738022T10 22	738022T12 22
25	738022T6 25	738022T8 25	738022T10 25	738022T12 25
30	738022T6 30	738022T8 30	738022T10 30	738022T12 30
35	738022T6 35	738022T8 35	738022T10 35	738022T12 35
40	738022T6 40	738022T8 40	738022T10 40	738022T12 40
45	738022T6 45	738022T8 45	738022T10 45	738022T12 45
50	738022T6 50	738022T8 50	738022T10 50	738022T12 50
55	738022T6 55	738022T8 55	738022T10 55	738022T12 55
60	738022T6 60	738022T8 60	738022T10 60	738022T12 60
65	738022T6 65	738022T8 65	738022T10 65	738022T12 65
70	738022T6 70	738022T8 70	738022T10 70	738022T12 70
75	738022T6 75	738022T8 75	738022T10 75	738022T12 75
80	738022T6 80	738022T8 80	738022T10 80	738022T12 80
90	738022T6 90	738022T8 90	738022T10 90	738022T12 90
100	738022T6 100	738022T8 100	738022T10 100	738022T12 100
110		738022T8 110	738022T10 110	738022T12 110
120	738022T6 120	738022T8 120	738022T10 120	738022T12 120



Auf Wunsch Fremdüberwacht
von M6 bis einschl. M12
lieferbar.
- "0" = reduzierte
Belastbarkeit

quality inspection from M6
including to M12 available on
demand.

- "0" = reduced load capacity

☞	500 ≥ 16 200 ≥ 45 100	500 ≥ 10 200 ≥ 25 100 ≥ 100 50	100 ≥ 50 50	50 ≥ 75 25
dk	13,6	17,8	21,9	24
k	3,3	4,4	5,5	6,6
t	2,1	2,7	3,4	4,2
c	1,2	1,5	2	2,4
Antrieb	TX30	TX40	TX50	TX55