



ISO 7380-1 A2
Flachrundkopfschrauben Innensechskant, Vollgewinde

ISO 7380-1
A2

ISO 7380-1 A2
Hexagon socket button head screws with fullthread

d	M 6	M 8	M 10	M 12
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
3				
4				
5				
6	7380126 6			
8	7380126 8	7380128 8		
10	7380126 10	7380128 10		
12	7380126 12	7380128 12	73801210 12	
14	7380126 14	7380128 14	73801210 14	
16	7380126 16	7380128 16	73801210 16	73801212 16
18	7380126 18	7380128 18	73801210 18	73801212 18
20	7380126 20	7380128 20	73801210 20	73801212 20
22	7380126 22	7380128 22	73801210 22	73801212 22
25	7380126 25	7380128 25	73801210 25	73801212 25
30	7380126 30	7380128 30	73801210 30	73801212 30
35	7380126 35	7380128 35	73801210 35	73801212 35
40	7380126 40	7380128 40	73801210 40	73801212 40
45	7380126 45	7380128 45	73801210 45	73801212 45
50	7380126 50	7380128 50	73801210 50	73801212 50
55	7380126 55	7380128 55	73801210 55	73801212 55
60	7380126 60	7380128 60	73801210 60	73801212 60
65	7380126 65	7380128 65	73801210 65	73801212 65
70	7380126 70	7380128 70	73801210 70	73801212 70
75	7380126 75	7380128 75	73801210 75	73801212 75
80	7380126 80	7380128 80	73801210 80	73801212 80
90	7380126 90	7380128 90	73801210 90	73801212 90
100	7380126 100	7380128 100	73801210 100	73801212 100
110		7380128 110	73801210 110	73801212 110
120	7380126 120	7380128 120	73801210 120	73801212 120



Auf Wunsch Fremdüberwacht
von M6 bis einschl. M12
lieferbar.
- "0" = reduzierte
Belastbarkeit

quality inspection from M6
including to M12 available on
demand.

- "0" = reduced load capacity

	500 ≥ 14 200 ≥ 45 100	500 ≥ 14 200 ≥ 25 100 ≥ 100 50	100 ≥ 50 50	50 ≥ 75 25
dk	10,5	14	17,5	21
k	3,3	4,4	5,5	6,6
t	2,08	2,6	3,12	4,16
Antrieb	SW 4	SW 5	SW 6	SW 8

ISO