

ISO 4762 A4  
Zylinderschrauben mit Innensechskant, Vollgewinde

ISO 4762 A4  
Hexagon socket head cap screws, fullthread

ISO 4762  
A4

Alternative Norm  
ehemals DIN 912

d	M 5	M 6	M 8	M 10	M 12
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
3					
4					
5	476245 5				
6	476245 6	476246 6			
8	476245 8	476246 8	476248 8		
10	476245 10	476246 10	476248 10		
12	476245 12	476246 12	476248 12	4762410 12	
14	476245 14	476246 14	476248 14	4762410 14	
16	476245 16	476246 16	476248 16	4762410 16	4762412 16
18	476245 18	476246 18	476248 18	4762410 18	4762412 18
20	476245 20	476246 20	476248 20	4762410 20	4762412 20
22	476245 22	476246 22	476248 22	4762410 22	4762412 22
25	476245 25	476246 25	476248 25	4762410 25	4762412 25
30	476245 30/30	476246 30	476248 30	4762410 30	4762412 30
35	476245 35/35	476246 35/35	476248 35	4762410 35	4762412 35
40	476245 40/40	476246 40/40	476248 40/40	4762410 40	4762412 40
45	476245 45/45	476246 45/45	476248 45/45	4762410 45/45	4762412 45
50	476245 50/50	476246 50/50	476248 50/50	4762410 50/50	4762412 50
55		476246 55/55	476248 55/55	4762410 55/55	4762412 55/55
60	476245 60/60	476246 60/60	476248 60/60	4762410 60/60	4762412 60/60
65	476245 65/65				
70	476245 70/70	476246 70/70	476248 70/70	4762410 70/70	4762412 70/70
75					
80	476245 80/80	476246 80/80	476248 80/80	4762410 80/80	4762412 80/80
85					
90		476246 90/90	476248 90/90	4762410 90/90	4762412 90/90
95					
100		476246 100/100	476248 100/100	4762410 100/100	4762412 100/100
120			476248 120/120		



Auf Wunsch Fremdüberwacht  
von M6 bis einschl. M24  
lieferbar.

quality inspection from M6  
including to M24 available on  
demand.

	500 ≥ 25 200 ≥ 60 100	500 ≥ 14 200 ≥ 45 100	500 ≥ 14 200 ≥ 25 100 ≥ 100 50	100 ≥ 50 50	50 ≥ 80 25
dk	8,5	10	13	16	18
k	5	6	8	10	12
Antrieb	SW 4	SW 5	SW 6	SW 8	SW 10

ISO