


ISO 4027 A2
Gewindestifte mit Innensechskant und Spitze

ISO 4027 A2
Hexagon socket set screws with cone point

ISO 4027
A2
Alternative Norm
ehemals DIN 914

d	M 2	M 2,5	M 3	M 4	M 5	M 6
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
2	402722 2					
3	402722 3	4027225 3	402723 3	402724 3		
4	402722 4	4027225 4	402723 4	402724 4	402725 4	
5	402722 5	4027225 5	402723 5	402724 5	402725 5	402726 5
6	402722 6	4027225 6	402723 6	402724 6	402725 6	402726 6
8	402722 8	4027225 8	402723 8	402724 8	402725 8	402726 8
10	402722 10	4027225 10	402723 10	402724 10	402725 10	402726 10
12	402722 12	4027225 12	402723 12	402724 12	402725 12	402726 12
14	402722 14	4027225 14	402723 14	402724 14	402725 14	402726 14
16	402722 16	4027225 16	402723 16	402724 16	402725 16	402726 16
18			402723 18	402724 18	402725 18	402726 18
20			402723 20	402724 20	402725 20	402726 20
22						402726 22
25			402723 25	402724 25	402725 25	402726 25
30			402723 30	402724 30	402725 30	402726 30
35			402723 35	402724 35	402725 35	402726 35
40			402723 40	402724 40	402725 40	402726 40
45				402724 45	402725 45	402726 45
50				402724 50	402725 50	402726 50
55					402725 55	402726 55
60					402725 60	402726 60
70						402726 70
80						402726 80
90						
100						
120						



	500	500	500 ≥ 30 200	500 ≥ 30 200	500 ≥ 25 200	200
dt	0,5	0,65	0,75	1	1,25	1,5
Antrieb	SW 0,9	SW 1,3	SW 1,5	SW 2	SW 2,5	SW 3

ISO