


ISO 10642

A2

Alternative Norm
ehemals DIN 7991



Auf Wunsch Fremdüberwacht
von M6 bis einschl. M24
lieferbar.
- "0" = reduzierte
Belastbarkeit

*quality inspection from M6
including to M24 available on
demand.*

- "0" = reduced load capacity

ISO 10642 A2 TX

Senkschrauben mit Innensechsrund und Vollgewinde

ISO 10642 A2 TX

Countersunk head screws six lobe drive with fullthread

| d | M 4 | M 5 | M 6 |
|-------------|---------------------|---------------------|---------------------|
| l/mm | Art. Nr. / Item no. | Art. Nr. / Item no. | Art. Nr. / Item no. |
| 10 | 106422T4 10 | 106422T5 10 | |
| 12 | 106422T4 12 | 106422T5 12 | 106422T6 12 |
| 14 | | | 106422T6 14 |
| 16 | 106422T4 16 | 106422T5 16 | 106422T6 16 |
| 20 | 106422T4 20 | 106422T5 20 | 106422T6 20 |
| 25 | | 106422T5 25 | 106422T6 25 |
| 30 | | 106422T5 30 | 106422T6 30 |

| | | | |
|----------------|------|------|------|
| l | 500 | 500 | 200 |
| dk | 8 | 10 | 12 |
| k | 2,3 | 2,8 | 3,3 |
| Antrieb | TX20 | TX25 | TX30 |