

ISO 4028

A4


Alternative Norm
ehemals DIN 915

ISO 4028 A4

Gewindestifte mit Innensechskant und Zapfen

ISO 4028 A4

Hexagon socket set screws with dog point



z = nach DIN,
Längenabhängig

z = acc. to DIN, dependent
on length

d	M 8	M 10	M 12	M 16	M 20
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
2					
3					
4					
5					
6	402848 6	4028410 6			
8	402848 8	4028410 8	4028412 8		
10	402848 10	4028410 10	4028412 10		
12	402848 12	4028410 12	4028412 12		
14	402848 14	4028410 14	4028412 14	4028416 14	
16	402848 16	4028410 16	4028412 16	4028416 16	
18	402848 18	4028410 18	4028412 18	4028416 18	
20	402848 20	4028410 20	4028412 20	4028416 20	4028420 20
25	402848 25	4028410 25	4028412 25	4028416 25	4028420 25
30	402848 30	4028410 30	4028412 30	4028416 30	4028420 30
35	402848 35	4028410 35	4028412 35	4028416 35	4028420 35
40	402848 40	4028410 40	4028412 40	4028416 40	4028420 40
45	402848 45	4028410 45	4028412 45	4028416 45	4028420 45
50	402848 50	4028410 50	4028412 50	4028416 50	4028420 50
55	402848 55	4028410 55	4028412 55	4028416 55	4028420 55
60	402848 60	4028410 60	4028412 60	4028416 60	4028420 60
70	402848 70	4028410 70	4028412 70	4028416 70	4028420 70
80	402848 80	4028410 80	4028412 80	4028416 80	4028420 80
90	402848 90	4028410 90	4028412 90	4028416 90	4028420 90
100	402848 100	4028410 100	4028412 100	4028416 100	4028420 100
120	402848 120	4028410 120	4028412 120		

	200	200 >= 25 100 >= 55 200 >= 60 100	100 >= 70 50	50 >= 80 25	50 >= 70 25
z	2	2,5	3	4	5
	4	5	6	8	10
dp	5,2	6,64	8,14	11,57	14,57
Antrieb	SW 4	SW 5	SW 6	SW 8	SW 10