

ISO 7380-1 A4
Flachrundkopfschrauben Innensechskant, Vollgewinde

ISO 7380-1
A4

ISO 7380-1 A4
Hexagon socket button head screws with fullthread

d	M 6	M 8	M 10	M 12
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
3				
4				
5				
6	7380146 6			
8	7380146 8	7380148 8		
10	7380146 10	7380148 10		
12	7380146 12	7380148 12	73801410 12	
14	7380146 14	7380148 14	73801410 14	
16	7380146 16	7380148 16	73801410 16	73801412 16
18	7380146 18	7380148 18	73801410 18	73801412 18
20	7380146 20	7380148 20	73801410 20	73801412 20
22	7380146 22	7380148 22	73801410 22	73801412 22
25	7380146 25	7380148 25	73801410 25	73801412 25
30	7380146 30	7380148 30	73801410 30	73801412 30
35	7380146 35	7380148 35	73801410 35	73801412 35
40	7380146 40	7380148 40	73801410 40	73801412 40
45	7380146 45	7380148 45	73801410 45	73801412 45
50	7380146 50	7380148 50	73801410 50	73801412 50
55	7380146 55	7380148 55	73801410 55	73801412 55
60	7380146 60	7380148 60	73801410 60	73801412 60
65	7380146 65	7380148 65	73801410 65	73801412 65
70	7380146 70	7380148 70	73801410 70	73801412 70
75	7380146 75	7380148 75	73801410 75	73801412 75
80	7380146 80	7380148 80	73801410 80	73801412 80
90	7380146 90	7380148 90	73801410 90	73801412 90
100	7380146 100	7380148 100	73801410 100	73801412 100
110		7380148 110	73801410 110	73801412 110
120	7380146 120	7380148 120	73801410 120	73801412 120



Auf Wunsch Fremdüberwacht
von M6 bis einschl. M12
lieferbar.
- "0" = reduzierte
Belastbarkeit

quality inspection from M6
including to M12 available on
demand.
- "0" = reduced load capacity

	500 ≥ 14 200 ≥ 45 100	500 ≥ 14 200 ≥ 25 100 ≥ 100 50	100 ≥ 50 50	50 ≥ 75 25
dk	10,5	14	17,5	21
k	3,3	4,4	5,5	6,6
t	2,08	2,6	3,12	4,16
Antrieb	SW 4	SW 5	SW 6	SW 8

ISO