

Till berörda kunder och samarbetspartners

Vårgårda 2021-01-04

CoP Conformity of Performance



Products of the brand Vatette, are made of DZR brass. All products have Swedish type approvals and meet the limit for lead precipitation of 5µg. This means that our Vatette products already today comply with the new product regulations for water and sewage systems that came into force on 1.1.2020.

The following types of products meet current standards for each product type as well as new Finnish requirements, in accordance with the Ministry of the Environment's ordinance

3/19 type approval of pipe fittings of brass and copper intended for water installations in buildings.

6/19 type approval of shut-off valves intended for water installations in buildings

| Compression fittings | Vatette-Plast, 12-40 mm |
|---|---|
| | Vatette, 6-54 mm |
| | Vatette-PE, 16-50 mm |
| | |
| Compression fittings for mounting bracket | c/c 150 mm: 12 mm – PE-X |
| | c/c 160 mm: 12-18 mm – PE-X, |
| | PE-RT, PE-RT/Alu/PE-RT och PB |
| | c/c 150 mm: 15-16 mm |
| | PE-X, PE-RT, |
| | PE-RT/Alu/PE-RT och PB |
| Vatette wall mounting system (40cc) | Wall plates and mounting brackets for copper, |
| | stainless steel, PEX, PB and MLC pipes |
| Vatette V6 wall mounting system (60cc) | Wall plates and mounting brackets for copper, |
| | stainless steel, PEX, PB and MLC pipes |
| Wall mounting system for connection to pipe in tube | Vatette wall plates, mounting brackets and fixtures |
| Ball valves | Vatette DN 12-22 |
| | Vatette automatic water leakage switch valve |
| | Securex 10-44 mm |
| | Vatette full flow valves DN10-50 |
| Ball valve with backflow protection | Securex 18, 19 & 23 mm |

www.vatette.se/typgodkannanden/

Best regards Villeroy & Boch Gustavsberg AB

Björn Rydetorp Product manager Markus Barkestedt Specialist Quality / Environment