


ISO 4029 A2
Gewindestifte mit Innensechskant und Ringschneide

ISO 4029 A2
Hexagon socket set screws with cup point

ISO 4029
A2
Alternative Norm
ehemals DIN 916

d	M 1,6	M 2	M 2,5	M 3	M 4	M 5
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
2	4029216 2	402922 2				
3	4029216 3	402922 3	4029225 3	402923 3	402924 3	
4	4029216 4	402922 4	4029225 4	402923 4	402924 4	402925 4
5	4029216 5	402922 5	4029225 5	402923 5	402924 5	402925 5
6	4029216 6	402922 6	4029225 6	402923 6	402924 6	402925 6
8	4029216 8	402922 8	4029225 8	402923 8	402924 8	402925 8
10		402922 10	4029225 10	402923 10	402924 10	402925 10
12		402922 12	4029225 12	402923 12	402924 12	402925 12
14		402922 14	4029225 14	402923 14	402924 14	402925 14
16		402922 16	4029225 16	402923 16	402924 16	402925 16
18				402923 18	402924 18	402925 18
20				402923 20	402924 20	402925 20
25				402923 25	402924 25	402925 25
30				402923 30	402924 30	402925 30
35				402923 35	402924 35	402925 35
40				402923 40	402924 40	402925 40
45					402924 45	402925 45
50					402924 50	402925 50
55						402925 55
60						402925 60
70						
80						
90						
100						
120						



	200	500	500	500 ≥ 30 200	500 ≥ 30 200	500 ≥ 25 200
dv	0,8	1	1,2	1,4	2	2,5
Antrieb	SW 0,7	SW 0,9	SW 1,3	SW 1,5	SW 2	SW 2,5

ISO