


ISO 7380-2 A4 mit Flansch TX  
Flachrundkopfschrauben Innensechsrund mit Flansch, Vollgewinde

ISO 7380-2  
A4

ISO 7380-2 A4 with flange TX  
Button head screws TX-drive flange with fullthread

d	M 6	M 8	M 10	M 12
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
3				
4				
5				
6	738024T6 6			
8	738024T6 8	738024T8 8		
10	738024T6 10	738024T8 10		
12	738024T6 12	738024T8 12	738024T10 12	
14	738024T6 14	738024T8 14	738024T10 14	
16	738024T6 16	738024T8 16	738024T10 16	738024T12 16
18	738024T6 18	738024T8 18	738024T10 18	738024T12 18
20	738024T6 20	738024T8 20	738024T10 20	738024T12 20
22	738024T6 22	738024T8 22	738024T10 22	738024T12 22
25	738024T6 25	738024T8 25	738024T10 25	738024T12 25
30	738024T6 30	738024T8 30	738024T10 30	738024T12 30
35	738024T6 35	738024T8 35	738024T10 35	738024T12 35
40	738024T6 40	738024T8 40	738024T10 40	738024T12 40
45	738024T6 45	738024T8 45	738024T10 45	738024T12 45
50	738024T6 50	738024T8 50	738024T10 50	738024T12 50
55	738024T6 55	738024T8 55	738024T10 55	738024T12 55
60	738024T6 60	738024T8 60	738024T10 60	738024T12 60
65	738024T6 65	738024T8 65	738024T10 65	738024T12 65
70	738024T6 70	738024T8 70	738024T10 70	738024T12 70
75	738024T6 75	738024T8 75	738024T10 75	738024T12 75
80	738024T6 80	738024T8 80	738024T10 80	738024T12 80
90	738024T6 90	738024T8 90	738024T10 90	738024T12 90
100	738024T6 100	738024T8 100	738024T10 100	738024T12 100
110		738024T8 110	738024T10 110	738024T12 110
120	738024T6 120	738024T8 120	738024T10 120	738024T12 120



Auf Wunsch Fremdüberwacht  
von M6 bis einschl. M12  
lieferbar.  
- "0" = reduzierte  
Belastbarkeit

quality inspection from M6  
including to M12 available on  
demand.

- "0" = reduced load capacity

☞	500 ≥ 12 200 ≥ 45 100	500 ≥ 14 200 ≥ 25 100 ≥ 100 50	100 ≥ 50 50	50 ≥ 75 25
dk	13,6	17,8	21,9	24
k	3,3	4,4	5,5	6,6
t	2,1	2,7	3,4	4,2
c	1,2	1,5	2	2,4
Antrieb	TX30	TX40	TX50	TX55

ISO